

New Product Announcement | High Operating Temperature Hose Reels

Heavy Duty Spring Retractable Hose Reels Series 5000 / 7000 / HD70000 / 80000 / 9000 / SD10000

Reelcraft's new high operating temperature hose reels are supplied with low pressure, rubber hoses for more extreme air temperature applications. The reels and hoses listed below are rated for temperatures ranging from -40 °F (-40 °C) to 212 °F (100 °C). The models listed are ideal for use with portable compressors that operate at high temperatures and high volumes of continuous air. **NOTE:** Not for use with water above 180 °F (82 °C).



7850 OLP-HTH

High Operating Temperature Hose Reels

Model with hose	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		Max Pressure		NPT(M) Hose Outlet	NPT(F) Reel Inlet
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in	in
Low Pressure Air Hose Reels Maximum temperature 212 °F (100 °C)												
5450 OLP-HTH	26	12	1/4	6	.470	12	50	15	300	21	1/4	3/8
7650 OLP-HTH	43	20	3/8	10	.630	16	50	15	300	21	1/4	1/2
HD76075 OLP-HTH	65	29	3/8	10	.630	16	75	23	300	21	1/4	1/2
81100 OLP-HTH	82	37	3/8	10	.630	16	100	23	300	21	1/4	1/2
7850 OLP-HTH	47	21	1/2	13	.770	20	50	15	300	21	3/8	1/2
7850 OLP-HTH121	47	21	1/2	13	.770	20	50	15	300	21	1/2	1/2
82100 OLP-HTH	95	43	1/2	13	.770	20	100	30	300	21	1/2	1/2
7925 OLP-HTH	47	21	3/4	19	1.06	27	25	8	300	21	3/4	3/4
83050 OLP-HTH	88	40	3/4	19	1.06	27	50	15	300	21	3/4	3/4
D83075 OLP-HTH	102	46	3/4	19	1.06	27	75	23	250	21	3/4	3/4
D9399 OLPBW-HTH	143	65	3/4	19	1.06	27	100	30	300	21	3/4	3/4
D84050 OLP-HTH	103	47	1	25	1.36	35	50	15	250	17	3/4	1
SD14050 OLP-HTH	125	57	1	25	1.36	35	50	15	250	17	3/4	1



82100 OLP-HTH

All reel models furnished with rubber high temperature hose. Temperature range: -40 °F to 212 °F (-40 °C to 100 °C)

High Operating Temperature Rubber Hoses

Part Number	Hose I.D.		Hose O.D.		End Fittings NPT(M)	Pressure		Length		Weight	
	in	mm	in	mm	in	psi	bar	ft	m	lbs	kg
601142-50	1/4	6	.470	12	1/4 x 1/4	300	21	50	15	4.65	2.11
601143-25	3/8	10	.630	16	1/4 x 1/4	300	21	25	8	4.58	2.08
601143-50	3/8	10	.630	16	1/4 x 1/2	300	21	50	15	9.15	4.15
601143-75	3/8	10	.630	16	1/4 x 1/2	300	21	75	23	13.73	6.23
601143-100	3/8	10	.630	16	3/8 x 1/2	300	21	100	30	18.3	8.3
601144-35	1/2	13	.770	20	3/8 x 1/2	300	21	35	11	7	3.18
601144-50	1/2	13	.770	20	3/8 x 1/2	300	21	50	15	10.5	4.76
601148-50	1/2	13	.770	20	1/2 x 1/2	300	21	50	15	10.5	4.76
601148-75	1/2	13	.770	20	1/2 x 1/2	300	21	75	23	15	6.8
601148-100	1/2	13	.770	20	1/2 x 1/2	300	21	100	30	20	9.07
601145-50	5/8	16	.940	24	3/4 x 3/4	300	21	50	15	15	6.8
601146-25	3/4	19	1.06	27	3/4 x 3/4	300	21	25	8	5.74	2.6
601146-50	3/4	19	1.06	27	3/4 x 3/4	300	21	50	15	11.48	5.21
601146-75	3/4	19	1.06	27	3/4 x 3/4	300	21	75	23	17.21	7.81
601146-100	3/4	19	1.06	27	3/4 x 3/4	300	21	100	30	22.95	10.41
601147-50	1	25	1.36	35	3/4 x 1	250	17	50	15	21.88	9.92
601149-50	1	25	1.36	35	1 x 1	250	17	50	15	21.88	9.92

Temperature range: -40 °F to 212 °F (-40 °C to 100 °C)

Refer to reelcraft.com for reel dimension information.



D9399 OLPBW-HTH



SD14050 OLP-HTH

Reelcraft Industries is
ISO 9001:2008
Certified Since 1996